

doorline-neatslope™



Instructions for use

Product codes: DNS6, DNS6A, DNS10, DNS10A, DNS16, DNS16A

Before use

- Remove and retain all packaging
- Ensure the ramp has not been damaged in transit or storage.
- Carefully read the instructions and warning texts before using ramps. Keep instructions for reference.
- The capacity of the ramp is 300kg (661lbs) assuming the ramp rests on the threshold.

To Deploy – Ramps **without** adhesive strip

- Clean and dry all ramp contact surfaces
- Check the fit of the ramp by placing it flush against the threshold
- Trim the ramp if necessary following the below “cutting to shape” instructions

To Deploy – Ramps **with** adhesive strip

- Clean and dry all ramp contact surfaces
- Check the fit of the ramp by placing it flush against the threshold
- Remove the ramp
- If cutting/modifying is required, do this before the next step (see cutting instructions below)
- Remove the tape on the underside of the ramp.
- Place the ramp on the clean surface
- Apply pressure to the ramp

Cutting To Shape - The ramps can be made smaller by following these steps

- Measure the threshold for height. (Remember to check the left, centre and right side of the door).
- Determine the cut position to achieve the required height. The guide lines on the top of the ramp can help ensure straight cuts. Use any hand saw or knife – follow all relevant health & safety procedures
- Place ramp in desired location and scribe for any vertical mouldings/door jams or uneven heights. Trim or notch ramp to fit (as described above) and sit ramp against threshold to check.

Maintenance

- If the ramps become damaged or slippery in any way they should not be used (contact supplier/manufacturer).
- The ramps may be cleaned with normal cleaning products and left to dry before use.
- Maximum recommended cleaning temperature 50°C, please enquire for further details on use with industrial cleaning machines

Recycling

- For disposal of this products, please liaise with a plastics recycling contractor

Warranty

- The ramps carry a comprehensive 2 year warranty for normal use, conditions apply.
- Use other than published/intended will void the warranty.



Code	Height	Length	Width	Capacity kg (st)	Weight kg (lbs)	Self Adhesive Y/N
DNS6	0.6cm (0.25ins)	6cm (2.4ins)	90cm (35.4ins)	300 (47)	0.3 (0.7)	N
DNS6A	0.6cm (0.25ins)	6cm (2.4ins)	90cm (35.4ins)	300 (47)	0.3 (0.7)	Y
DNS10	1cm (0.4ins)	10cm (3.9ins)	90cm (35.4ins)	300 (47)	0.75 (1.7)	N
DNS10A	1cm (0.4ins)	10cm (3.9ins)	90cm (35.4ins)	300 (47)	0.75 (1.7)	Y
DNS16	1.6cm (0.6ins)	15cm (5.9ins)	90cm (35.4ins)	300 (47)	1 (2.2)	N
DNS16A	1.6cm (0.6ins)	15cm (5.9ins)	90cm (35.4ins)	300 (47)	1 (2.2)	Y

Ramp Centre is a registered trademark of Enable Access AL9 5SD. We undertake a policy of continual review and research, which may lead to changes in product appearance and specification.

For technical support or details on your nearest stockist please call 0870 27 99 4 99