

Product data sheet





Information

Designation Arsis 135° angled grab bar, 200 x 200 mm, Anthracite grey epoxy


aluminium

Reference 049732

Product advantages

- + Elliptic tube for an improved grip.
- + Possible to fit it "to the right" or "to the left".
- + Elegant and design shape.
- + Corrosion resistant warranty.

Description



2 fixing points.

Symmetrical 200 x 200 mm.

Elliptical tube in anthracite grey epoxy-coated aluminium.

Anthracite grey resin cover plates.

Wall fixings included.

Design coordinated with all ARSIS Comfort items.

Perfectly suitable for use in the hospitality industry.

Technical characteristics

Finish
Dimensions
Diameter Ø
Material
Gross weight
CE Marking: safe load
Laboratory tests
Net weight

Epoxy-coated 200 x 200 mm 38 x 25 mm Aluminium 0.500 kg 150 kg 225 kg 0.450 kg 3563390497326



Custom code Technical sheet 7615200000

A04984002_IND_10

Fixing and maintenance advices

Recommended height for the horizontal part: 800 mm from the ground. Grab bars provide support and added safety if properly fitted in accordance with our technical instructions. Careful consideration and selection of the appropriate wall fixings according to the wall-mounted support is required to ensure the long life of your accessory. The use of stainless steel screws (Ø 4 mm) is highly recommended to prevent corrosion in damp environment. Before drilling, physically hold the product against the wall at desired position and mark the hole locations. All the fixing points must be respected. After installation and before use, make sure that all fixing screws are tightened securely. DO NOT use the grab bar as a step. DO NOT sit on or hang from the grab bar.

Maintenance

IMPORTANT: To ensure the sustainability of the product and user safety, we recommend using a solution made of mild soap for cleaning. CAUTION: DO NOT USE cleaning products made of: etones, hydrocarbons, acids, bases, esters and ethers. After use of a cleaning product, make a rinsing in the clear water.

Confort of use

Function		Characteristics		
Support	***	Horizontal	***	
Raising	***	Vertical	☆☆☆	
Transfer	***	Diagonal	***	
		Corrosion resistant	***	
Type of Use		Location of Use		
Bath	***	Medical facilities	***	
Shower	***	ERP/IOP	***	
Toilet	***	Hotels	***	
Cloakroom/Changeroom	***	Private homes	***	
		Workplaces	***	

Fiche produit mise à jour le : 10/01/2023