

Shallow Bowl Kitchen Sink Insulation PadTechnical Data SheetExpanded Grey FR Neoprene Sponge Rubber – 6mm Thick

<u>PROPERTIES</u>	<u>AVERAGE VALUE</u>
ASTM D1056	2C2
Density	160 Kg m3
Compression Deflection 25% (35 – 63)	50 kpa
Shore Hardness “00” Scale	45-50
Elongation – Minimum	> 200%
Temperature Range (Constant)	-40 deg C / +80 deg C
Temperature Range (Intermittent)	+ 120 deg C
Water Absorption	< 5% vol
Tensile Strength	> 500 kpa
Flame Resistance	FMVSS302 UL 94 HF1
Environmental Protection	CFC & HCFC Free
Colour	Grey

*The above figures are average values and should be considered as guidelines and not specification.
While reasonable care has been taken to ensure that this data is representative. Independent 4 Life Limited does not warrant or otherwise guarantee, expressly or impliedly, the suitability, accuracy, reliability or completeness of the information*

Please see page 2 for installation Instructions.

Installation Instructions for 4Life Self Adhesive Heat Insulation Pad for Shallow Bowl
Kitchen Sinks - 500x500mm or 300x400mm



Thank you for your purchase of a 4Life Self Adhesive Heat Insulation Pad for Shallow Bowl Kitchen Sinks - 500x500mm or 300x400mm

Please follow the installation instructions carefully:

- 1) Clean, degrease and dry the underside of your kitchen sink (If there is sound insulation present, the Heat Insulation Pad can be applied over the top of the sound insulation)
- 2) Create a template of the underside of your kitchen sink (make sure to include the waste)
- 3) Carefully cut around the template using a sharp pair of scissors or a suitable knife
- 4) Peel back the shiny protective waxed paper film exposing the self adhesive backing
- 5) Adhere the sink pad to the underside of the kitchen sink.

Should you have any issues or questions, please contact Independent 4 Life's technical department on 0800 500 3001