




Geberit AquaClean Mera Care WC complete solution, floor-standing WC



Application purposes

- For convenient and odourless toilet use
- For gently cleaning the anal and vaginal areas with water

Characteristics

- Hybrid hot water system with continuous flow heater and storage water heater
- Anal shower with double-nozzle WhirlSpray shower technology
- Separate Lady shower nozzle in protected park position
- Adjustable shower water temperature
- Spray intensity can be set to five different levels
- Spray arm can be set to five different positions
- Adjustable oscillating spray (automatic forward and reverse motion of the spray arm)
- Automatic pre- and postrinsing of the spray nozzle with fresh water
- Descaling programme
- Rimless WC ceramic appliance featuring TurboFlush flush technology
- Washdown WC with special glaze KeraTect
- User detection
- Odour extraction unit with run-on function
- Odour extraction with ceramic honey comb filter can be activated
- Dryer can be activated
- Dryer arm can be extended
- Adjustable dryer temperature
- WC seat ring with SoftClosing
- WC seat ring, fixed, for absorption of lateral forces
- Premounted sound insulation
- Functions and settings via remote control
- Four user profiles can be programmed
- Compatible with Geberit AquaClean app
- External water supply connection, possible with accessories
- Mains connection with flexible three-wire sheathed cable, on the right side, hidden behind the WC ceramic

- External mains connection with power outlet on the right possible
- With integrated exposed cistern
- Seat height adjustable between 44 and 56 cm
- Toilet flush can be started by remote control
- Approval in accordance with (DIN) EN 1717 / (DIN) EN 13077

Technical data

Protection class	I
Protection degree	IPX4
Nominal voltage	230 V AC
Mains frequency	50 Hz
Power consumption	2000 W
Power consumption standby	≤ 0.5 W
Flow pressure	0.5–10 bar
Operating temperature	5–40 °C
Water temperature, adjustment range	34–40 °C
Flush volume, factory setting	6 and 4 l
Calculated flow rate	0.03 l/s
Minimum flow pressure for calculated flow rate	0.5 bar
Spray time	30–50 s
Maximum load WC seat	150 kg

Scope of delivery

- Female socket for mains connection
- Spray shield
- Descaling agent, 125 ml
- Cleaning set
- Connection set for WC, ø 90 mm
- Remote control with wall-mounted case and battery CR2032
- Fastening material
- Wall-mounted control panel for touchless activation

Art. no.	Surface / colour	
146.242.11.1	AquaClean Mera Care: white alpine Cladding flushing cistern: high-pressure laminate white	NEW

Accessories

- Geberit S-bend set for floor-standing WC



-
- This product is supplied with the Geberit AquaClean descaling agent and the Geberit AquaClean cleaning agent. These consumables contain classified hazardous substances. Information, instructions and measures for handling hazardous substances safely can be found in the appendix or at www.geberit.com.
 - This product is only available via the Geberit Care Team. Please contact us for more information.
 - Replacement of art. no. 185.200.11.1