# Mira Advance Flex Extra





Thermostatic Electric Shower

Designed for simple wireless connection to drainage pumps.

### **Product Information**

Description	Colour	Product No.
Mira Advance Flex Extra 8.7kW	White/Chrome	1.1785.005

### Features & Benefits

### Temperature contro

Reduces risk of scalding and ensures user safety

### Easy to fi

Integral wired or bluetooth wireless connection to drainage pump for hassle-free installation

### Easy to service

Easy filter access

Built in fault diagnostics

### For your customer

Easily accessible controls free from clutter with high contrast on critical touch points. RNIB Approved Gold awarded

Large easy press power button

Audible and tactile features for the visually impaired user

Light touch controls

4 different maximum temperature settings

 $\label{eq:mira-opti-flo-pro} \mbox{Mira-Opti-flo-Pro} \mbox{\footnote{technology-for-consistent-performance}}$ 

Mira Clearscale  $Pro^{TM}$  technology that reduces limescale build up, meaning Advance will outlast the competition

Anti-glare matte finish panel

Extra long easy to use slide bar with patented friction-grip showerhead holder

110mm showerhead with 3 spray modes

Easy clean removable spray plate

Wireless Bluetooth® enabled to pair with Whale pump for unique Flood Reduction System





### **Tech Details**

Control type: Thermostatic

Power options: 8.7kW 240V AC (8.0kW 230V AC)

Supply voltage:  $230v \pm 10\%$ 

Supply rating: 40 amp (8.7kW); 45 amp (9.8kW)

Terminal Block connections: Maximum 16mm<sup>2</sup>

Water entry points: Right (rising, falling & rear)

Cable entry points: Right (rising, falling & rear)

Inlet connections: 1/2" BSP male or 15mm compression

Outlet connections: 1/2" BSP Male

Supply Conditions

Minimum maintained pressure: 0.5 bar (5 metre head),

(1.0 bar BEAB Care)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

Temperature stability:  $\pm 1$ °C

Phased shutdown: Yes

Factory set to safe max temp: Adjustable to 4 different max temp

settings (41°C - 48°C)

Wide range of accessories available at www.mirashowers.co.uk

BEAB CARE approved

BEAB approved

Energy Efficiency: Class A

RNIB Approved Gold awarded

Kiwa certified

WRAS approved



Intertek









## **Dimensions**



