


Geberit AquaClean Sela WC complete solution, wall-hung WC



Application purposes

- · For convenient toilet use
- · For gently cleaning the anal and vaginal areas with water

Characteristics

- · Water heating via continuous flow heater
- Anal shower with WhirlSpray shower technology
- Separate Lady shower nozzle in protected park position
- Adjustable shower water temperature
- Spray intensity can be set to five different levels
- · Spray arm can be set to five different positions
- Adjustable oscillating spray (automatic forward and reverse motion of the spray arm)
- · Automatic pre- and postrinsing of the spray nozzle with fresh water
- Descaling programme
- Rimless WC ceramic appliance featuring TurboFlush flush technology
- Washdown WC
- User detection
- WC seat ring and WC lid with soft-closing mechanism
- WC lid with SoftOpening
- Activation of the orientation light via brightness sensor
- · Orientation light can be set in seven colours
- Functions and settings via remote control
- Four user profiles can be programmed
- Compatible with Geberit Home App

Scope of delivery

- Water supply connection set for Sigma and Omega concealed cisterns
 12 cm, installation height 112 cm
- Female socket for mains connection
- Sound insulation set
- · Spray shield

Water supply connection on the left, hidden behind the WC ceramic

- Mains connection with flexible three-core sheathed cable, on the right side, hidden behind the WC ceramic
- External water supply connection on the left possible with accessories
- External mains connection with power outlet on the right possible
- Approval in accordance with (DIN) EN 1717 / (DIN) EN 13077

Technical data

Protection degree	IPX4
Protection class	1
Nominal voltage	230 V AC
Mains frequency	50 Hz
Power consumption	1850 W
Power consumption standby	≤ 0.5 W
Flow pressure	0.5–10 bar
Operating temperature	5–40 °C
Water temperature, adjustment range	34–40 °C
Calculated flow rate	0.02 l/s
Minimum flow pressure for calculated flow rate	0.5 bar
Spray time	50 s
Maximum load WC seat	150 kg

Descaling agent, 125 ml

- Cleaning set
- Connection set for WC, ø 90 mm
- Remote control with wall-mounted case and battery CR2032
- Fastening material

Art. no. Colour / surface 146.220.11.1 WC ceramic appliance: white / KeraTect Design cover: white

146.220.21.1	WC ceramic appliance: white / KeraTect
	Design cover: gloss chrome-plated

Accessories

- Wall-mounted control panel for Geberit AquaClean Sela
- Wall-mounted control panel, touchless, for Geberit AquaClean
- Interface module 4.1 V for Geberit AquaClean Mera / Sela
- Interface module 12 V for Geberit AquaClean Mera/Sela





• This product is supplied with the Geberit AquaClean descaling agent and the Geberit AquaClean cleaning agent. These consumables contain classified hazardous substances. Information, instructions and measures for handling hazardous substances safely can be found in the appendix or at www.geberit.com.