

# PRESSALIT.

Product	MATRIX manual basin unit		
Item number	R4825000		
	EAN: 5708590349671		
Colour	White		
Product description	MATRIX brackets are tailor made for MATRIX wash basins. They are available in electrically and manually height adjustable versions, as well a fixed versions, all of them with a hygienic cover to conceal the plumbing installation		
	MATRIX wash basin bracket, wall-mounted, with white installation cover and incl. concealed flexible feed/waste system and shallow trap. Manually height adjustable 200 mm with crank handle Incl. fixing bolts for wash basin (Can only be used with MATRIX MEDIUM wash basins, R2120/R2121). Materials: Powder-coated steel and polystyren Excl. mounting kit.		
Adjustability	Height adjustable		
Adjustment height	200 mm		
Product capacity	Maximum load: 150 kg. Suitable for wash basins weighing no more than 25 kg. When the wash basin is loaded with 150 kg, each wall fastener will be carrying 60 kg. Wash basin brackets need to be able to carry the weight of the wash basin, as well as support the weight of the person who is leaning against the wash basin or who is using the wash basin to rise from seated position. <b>Neither wash basin nor wash basin bracket are intended to carry the full body</b> <b>weight of a person</b> , and the test methods applicable to wash basin brackets reflect this: ISO 17966 prescribes a static test on the front edge of the wash basin at 75% of maximum user weight, i.e. when the maximum load on a wash basin bracket is given as 150 kg and the wash basin weighs 25 kg, it is – according to ISO 17966 – the equivalent of a user weighing 167 kg leaning on the front edge of the wash basin.		
Materials	Powder-coated steel and polystyren.		



#### PRESSALIT.

Product	MATRIX manual basin unit			
Item number	R4825000			
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.			
Cleaning	<ul> <li>VALUE &amp; MATRIX wash basin brackets. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use corrosive or abrasive cleaners as it may result in the surface being damaged. For surface disinfection, chlorine-based disinfectants may be used according to the product specification and safety precautions for these products.</li> <li>The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.</li> <li>DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Klorilli</li> <li>NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200</li> <li>The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.</li> </ul>			
Declaration of conformity	This product is in compliance with all relevant requirements of regulation (EU) 2017/745 on medical devices. It also complies with all relevant requirements in the Council Directive 2006/42/EC (of 17 May 2006) on machinery.			



# PRESSALIT.

MATRIX manual basin unit Product Item number R4825000 Installation in different wall types Concrete >B25 V8605 - Mounting kit, 4 coach screws Ø10 x 70, plugs . ß 3 SX12, with grey screw covers. ° ⊽ ß  $\triangleright$ 1 в. To be ordered separately. .00 Solid Brick >= Mz12 V8605 - Mounting kit, 4 coach screws Ø10 x 70, plugs SX12, with grey screw covers. To be ordered separately. ţ Solid Sand Lime Brick >= HIz12 Π Ŧ V8605 - Mounting kit, 4 coach screws Ø10 x 70, plugs SX12, with grey screw covers. To be ordered separately. F **Aerated Concrete P4** V8655 - Mounting kit, 4 coach screws Ø10 x 70, plugs GB14, with grey screw covers. To be ordered separately. Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8605 - Mounting kit, 4 coach screws Ø10 x 70, plugs SX12, with white screw covers. NB! Plugs are not needed. To be ordered separately.



# PRESSALIT.

Product Item number	MATRIX manual basin unit R4825000	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	<b>Drywall (2 x 12,5 mm) water-resistant</b> Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	

It is the responsibility of the installer to ensure that suitable wall fasteners are used.



#### www.pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

