

PRESSALIT.

Product	SCT 1000 shower change table, fixed height	
Item number	R8406000	
	VVS:777545340	
	EAN:5708590294810	
	HMI: 88216	
	NBS:N13:40,375	
	FDA: INT/D124320	
Colour	White Say	
	×12 1400 -	
Product description	Pressalit offers a variety of mobile and wall-hung, height-adjustable and fixed height shower and changing tables of high quality. They are designed to provide a stable platform for showering and changing adults and children with reduced mobility. These tables can be used in schools, institutions, hospitals and private homes and are all designed to be durable, comfortable and easy to clean. The design and flexibility of the tables ensures optimal working conditions for the carer as well as a high level of comfort and safety for the user.	
	SCT 1000 shower change table, fixed height. Foldable. Incl. safety rail. Outer measurements 747 mm x 1400 mm. Materials: Rilsan coated steel and PVC-coated canvas (phthalate free). Excl. mounting kit.	
Adjustability	Fixed mounting	
Product capacity	Maximum load: 150 kg. When the table is loaded with 150 kg, each mounting bolt supports 46 kg.	
Materials	The table is made from practical and durable PVC canvas which is phthalate free. The frame is powder-coated steel.	
Ergonomy	Foldable.	
Features	The integrated gas cylinders enable the table to be folded out of the way when not in use to maximise floor space in front of the unit. Splash curtain (optional) for the nursing bench protects the carer against splashing.	





_

PRESSALIT.

Product Item number	SCT 1000 shower change table, fixed height R8406000
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. NOTICE If the product is installed in an atmosphere heavy in salt or chloride, the warranty will be reduced from the normal 3 years to 1 year. Salt and chloride have a corrosive effect on the products components and will cause a decrease in the life expectancy of the product. The damaging effects can, however, be reduced if the product is showered with tap water on a daily basis.
Cleaning	SCT 1000 & 2000. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.
	The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.
	DISINFECTANTS: Clinimax Difficil-S Erisan OXY+
	NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200
	The product must be wiped down with a soft rag wrung out in clear water immediate after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.
Declaration of conformity	This product is in compliance with all relevant requirements of regulation (EU) 2017/745 on medical devices.



PRESSALIT.

Product Item number	SCT 1000 shower change table, fixed height R8406000	
Installation in	different wall types	
	Concrete >B25 V8611 - Mounting kit, 9 hex screws Ø10 x 70 - plugs SX12. To be ordered separately.	
	Solid Brick >= Mz12 V8611 - Mounting kit, 9 hex screws Ø10 x 70 - plugs SX12. To be ordered separately.	Image: state
	Solid Sand Lime Brick >= HIz12 V8611 - Mounting kit, 9 hex screws Ø10 x 70 - plugs SX12. To be ordered separately.	
	Aerated Concrete P4 V8661 - Mounting kit, 8 bolts M5 x 50 - plugs FTP K 6. To be ordered separately.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8611 - Mounting kit, 8 screws Ø5 x 50 - plugs SX8. NB! Plugs are not needed. To be ordered separately.	



PRESSALIT.

Product Item number	SCT 1000 shower change table, fixed height R8406000	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (9 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Wall fasteners (9 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant	
	Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	$\underline{\land}$

It is the responsibility of the installer to ensure that suitable wall fasteners are used.



www.pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

