

Product Item number	SCT 3000 shower change table, electrically height adjustable R8582313299	
	VVS:777543448 EAN:5708590374093 HMI: 130167	
Colour	Sapphire blue (RAL 5003)	
Product description	Pressalit offers a variety of mobile and wall-hung, height-adjustable and fixed height shower and changing tables of high quality. They are designed to provide a stable platform for showering and changing adults and children with reduced mobility. These tables can be used in schools, institutions, hospitals and private homes and are all designed to be durable, comfortable and easy to clean. The design and flexibility of the tables ensures optimal working conditions for the carer as well as a high level of comfort and safety for the user.	
	The SCT 3000 series has a stylish and award-winning design focused on comfort and ease of use.	
	SCT 3000 shower change table, powered, height adjustable 700 mm; from 300 mm - 1000 mm, with wired hand control Foldable. Incl. safety rail and water collection tray with integrated outlet. Surface length 1300 mm, outer measurements 1057 mm x 1410 mm. Materials: Powder-lacquered stainless steel, aluminium, polyurethane foam and polystyrene. Excl. mounting kit.	
Adjustability	Height adjustable	
Adjustment height	700 mm	
Product capacity	Maximum load: 200 kg. When the table is loaded with 200 kg, each mounting bolt supports 26 kg This product has been tested statically with a load of 500 kg as the IEC 60601- standard requires testing with safety factor 2.5.	
Speed	Speed up mm: 15 mm/s Speed down mm: 20 mm/s	
Noise level	48 dB	



Product SCT 3000 shower change table, electrically height adjustable R8582313299	
Makadala Ali 12 I II II I I I I I I I I I I I I I I	
Materials Aluminium, polyurethane foam, plastics, powder-laquered steel.	
• The ergonomically designed safety rails have a practical lower central section which provides better access and work environment for the carer while transplants showering, drying, changing and dressing the user.	
One hand operated safety rails allows the carer to maintain eye contact as physical contact with the user during the whole process.	well as
Easy to clean, smooth contact surfaces which do not collect dirt and bacter	ia.
• A water collection tray with integrated water outlet prevents water from spla carers or the floor. The flexible hose attached to the center mounted outlet or water collection tray, can be connected to either an outlet in the floor or on the	f the
The slightly curved shape makes the table comfortable and safe to lie on.	
Adjustable neck support which can be moved to either end of the 1800 mm and changing tables.	shower
The integrated gas cylinders enable the table to be folded out of the way which in use to maximize floor space.	nen not
The powered shower change table is supplied with a wired hand control. The buttons clearly indicate "up" and "down".	ne red
The wired hand control comes with a practical holder for placement on the	wall.
Mains connection (V) 230	
Actuator (motor) LA40CS Careline (Linak) 4000 N, IPX6	
Control box SMPS14 Careline (Linak), IPX6	
Wired remote control HB3 (Linak), IPX6	
Power consumption (maximum load) Power consumption by maximum load, watt: 144 W Power consumption by standby: 2 W	



Product Item number	SCT 3000 shower change table, electrically height adjustable R8582313299
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. NOTICE If the product is installed in an atmosphere heavy in salt or chloride, the warranty will be reduced from the normal 3 years to 1 year. Salt and chloride have a corrosive effect on the products components and will cause a decrease in the life expectancy of the product. The damaging effects can, however, be reduced if the product is showered with tap water on a daily basis.
Cleaning	SCT 3000. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Clinell Universal Wipes Clinel Sporidical Wipes Chlor-Clean Tablets WipeClean Ethanol Disinfection 80% Wetwipe Ethanol Disinfection 70% (wetwipe) NON-DISINFECTANTS: Wetwipe Universal The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate. DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that chalky deposits be removed from wall tracks and other aluminum parts using a solution of three parts 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts
Declaration of conformity	must be wiped over with a damp cloth wrung out in clear water. This product is in compliance with all relevant requirements of regulation (EU) 2017/745 on medical devices. It also complies with all relevant requirements in the Council Directive 2006/42/EC (of 17 May 2006) on machinery and the Council Directive 2011/65/EC on RoHS.



PRESSALIT.

Prod	luct
Item	numbei

SCT 3000 shower change table, electrically height adjustable

R8582313299

Installation in different wall types

Concrete >B25 V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.	
Solid Brick >= Mz12 V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.	
Solid Sand Lime Brick >= HIz12 V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.	
Aerated Concrete P4 V8658 - Mounting kit, 6 coach screws Ø10 x 70 - plugs GB14. To be ordered separately.	
Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. NB! Plugs are not needed. To be ordered separately.	



Product Item number	SCT 3000 shower change table, electrically height adjustable R8582313299	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant	
	Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	

It is the responsibility of the installer to ensure that suitable wall fasteners are used.







www.pressalit.com