



Independent 4 Life

£24.17 Inc. VAT

Hydraelectric WRAS Approved (PEX) Flexible Water Hoses, 500mm Length - 15mm Female Comp x M10 - Pair

Product Code: WRAS-500-PEX

Product Images



Description

(PEX) Flexible hoses for height adjustable washbasin lifts or static installations.

www.independent4life.co.uk | info@independent4life.co.uk | Tel: 0800 500 3001 | VAT No: 942447711

EORI GB942447711000

These hoses are made with stainless steel over braid and liner manufactured from cross-linked polyethylene (PEX).

Designed to comply with the UK's stringent demands in providing flexible hose connections in health care and public service markets.

Providing the safe and taint free conveyance of potable water supplies for domestic and commercial plumbing applications.

WRAS approved with 15mm female compression fitting and M10 Monobloc tap connectors, these 500mm long hoses are suitable for the Granberg Basicline and Designline lifting systems.

Key benefits:

- Reduction in the risks associated with micro bacterial colonisation and potential for cross infections
- The liner is designed to reduce the growth of waterborne micro-organisms compared to other materials
- All materials have been tested and approved to BS 6920 in accordance with Water Regulation Advisory Scheme (WRAS) for both hot and cold water
- Unique green tracer band for easy identification against other materials
- Robust construction with excellent abrasion and crush resistance

Technical details:

- Manufactured by Hydraelectric - ISO 9001: 2008 compliant as certified by British Standards Institute under certification number FM592672
- All materials have been tested and approved to BS 6920 in accordance with Water Regulation Advisory Scheme (WRAS) for both hot and cold water
- 2x Flexible PEX braided hoses
- Length (mm): 500
- Bore (mm): 8
- Hose Ref. DN8
- Connections: 15mm Female compression
- Connections: M10 for monbloc taps
- Designed for use with hot and cold potable water supplies
- Min. Bend radius 35mm by which the hose can be bent without causing excessive stress to the hose fabric or kink.
- Working pressure at 20°C Bar: 12
- Working pressure at 65°C Bar: 6
- Security pressure at 20°C Bar: 18
- Flow rate at 3 Bar (Ltr/Min): 28

Warranty:

- 1 year manufacturer warranty

Note:

- The critical length is the distance between hose mating faces. This must be 10% greater than the actual distance between the two corresponding fixed mating parts to avoid tensile stress whilst in service
- See PDF Installation instructions for more information

Additional Information

Manufacturer	Hydraelectric
Component	Flexible Feeds
Hose Length (mm) / Application	500 / Water Feeds
Technologies	PEX - Healthcare DN8 Hose
Approvals	WRAS Approved