



Independent 4 Life

AWS Grooved High Flat AL Door THR, for Floorsprings 177.8 W x 12.7 H - Choice of Length 914 to 3048mm

From: £126.90
To: £1,190.80
Inc. VAT


Product Code: 4LA840126

Product Images




Product Options

Width x Height x Length ft / mm




177.8 W x 12.7 H x 3ft / 914mm L £105.75

177.8mm wide high flat threshold, 12.7mm high. Aluminium, mill finish. 914mm (3ft) length. 6.4mm thick, for use with floor springs in new applications (undrilled).




177.8 W x 12.7 H x 4ft / 1219mm L £136.66

177.8mm wide high flat threshold, 12.7mm high. Aluminium, mill finish. 1219mm (4ft) length. 6.4mm thick, for use with floor springs in new applications (undrilled).




177.8 W x 12.7 H x 6ft / 1829mm L £198.49

177.8mm wide high flat threshold, 12.7mm high. Aluminium, mill finish. (6ft) 1829mm length. 6.4mm thick, for use with floor springs in new applications (undrilled).



177.8 W x 12.7 H x 7ft / 2134mm L £229.40

177.8mm wide high flat threshold, 12.7mm high. Aluminium, mill finish. (7ft) 2134mm length. 6.4mm thick, for use with floor springs in new applications (undrilled).



177.8 W x 12.7 H x 10ft / 3048mm L £322.03

177.8mm wide high flat threshold, 12.7mm high. Aluminium, mill finish. 3048mm (10ft) length. 6.4mm thick, for use with floor springs in new applications (undrilled).

Description

Aluminium high utility plain grooved door threshold, for use with floorsprings in new applications. Constructed from 6.4mm thick aluminium with a 12.7mm height.

Key benefits:

- For internal and external doors

- Heavy duty
- Aluminium mill finish
- Grooved top
- Simple to install
- Fixing holes undrilled
- Ideal for commercial and domestic installations
- Non flammable

Technical details:

- Choice of Length: 914mm (3 ft), 1219mm (4 ft), 1829mm (6 ft), 2134mm (7 ft) and 3048mm (10 ft)
- Width: 177.8mm (7")
- Height: 12.7mm (0.5")
- Material: 6.4mm (0.25") thick aluminium

Installation Instructions:

- Measure and cut threshold to size as required
- Notch as necessary, to suit door frame
- Caulk underneath and around edges of threshold for moisture control
- Attach threshold to floor surface with screws provided

Additional Information

Manufacturer	AWS
Application	12.7mm High Flat
Length (mm / feet)	914 / 3', 1219 / 4', 1829 / 6', 2134 / 7', 3048 / 10'
Width (mm / inches)	177.8 / 7"
Supplied Pre-drilled	No