



Independent 4 Life

Ultralight-Combi Folding & Telescopic, Standard 19cm Channel Ramps - 207 & 276cm Overall Length (Pair)

From:	£760.81
To:	£1,708.67
Inc. VAT	

Product Code: PC21-3-PC28-3

Product Images



Product Options

Product Code / Internal channel width / Overall length (cm)

PC21-3 / Standard 19 / 207cm

£634.01



Ultralight-Combi, unique lightweight channel ramps that are both folding and telescopic. Good for bridging door threshold with unequal levels each side and for bridging uPVC door thresholds. Overall length 207cm (6ft 9"), length of telescopic section 132cm (5ft 2"), length hinged section 75cm (30"), internal channel width 19cm (8"). Max. load (pair) 300kg (47st). Weight of each half 6.4kg (14lbs). Stored Dimensions L x W x D - 76 x 24.5 x 13cm (30 x 10 x 5").

PC28-3 / Standard 19 / 276cm

£789.88



Ultralight-Combi, unique lightweight channel ramps that are both folding and telescopic. Good for bridging door threshold with unequal levels each side and for bridging uPVC door thresholds. Overall length 276cm (9ft 11"), length of telescopic section 176cm (6ft 9"), length hinged section 100cm (39"), internal channel width 19cm (8"). Max. load (pair) 250kg (39st). Weight of each half 8.4kg (19lbs). Stored Dimensions L x W x D - 102 x 24.5 x 13cm (40 x 10 x 5").

Description

Ultralight-Combi™ are unique lightweight channel ramps that are both folding and telescopic.

The channel ramps can be used straight or folded over a threshold and offer the greatest flexibility for access.

Available in two sizes with an overall length of 207cm (6ft 9") and 276cm (9ft 1") with a channel width of 19cm (7.48").

Key benefits:

- Can be used straight or folded over a threshold depending on your requirements
- 5cm (2") Low kerbs and long bevel sides greatly increase clearance for scooters and power chairs
- A good choice for bridging a threshold with unequal levels each side
- Compact for storage and stowing in a vehicle
- Excellent solution for going up and over uPVC door thresholds
- The two halves can be used at different lengths from each other, great for use on cross-slopes
- Great for handling cross-slopes, where each half can be adjusted to any length and set at different lengths from each other as required
- Lightweight

- Designed, manufactured, and stocked in the UK

Technical details:

- Both ramps have an Internal track width of: 19cm (7.48")
- Both ramps have a kerb height of: 5cm (2")

Product Code: PC21-3

- Max. length: 207cm (6ft 9")
- Telescopic length: 132cm (52")
- Hinged length: 75cm (30")
- Stored dimensions: 76 x 24.5 x 13cm (30 x 10 x 5")
- Capacity (Pair): 300kg (47st)
- Weight each half: 6.5kg (14lbs)

Product Code: PC28-3

- Max. length: 276cm (9ft 1")
- Telescopic length: 176cm (69")
- Hinged length: 100cm (39")
- Stored dimensions: 102 x 24.5 x 13cm (40 x 10 x 5")
- Capacity (Pair): 250kg (39st)
- Weight each half: 8.4kg (19lbs)

Warranty:

- 2-year manufacturer warranty

Manufacturer product codes:

- PC21-3, PC28-3

Additional Information

Manufacturer	RampCentre
Ramp Width (cm / inches)	Int. Channel 19 / 7.48"
Application / Ramp Type	Channel Ramps (Pair)
Dead Weight (kg / lbs)	5.0 to 9.99 to 11.02 / 21.83
Ramp Material	Aluminium
Handrails	No Handrails