



Independent 4 Life

Ultralight-Combi Wide Folding & Telescopic, Wide 25cm Channel Ramps, 210 & 300cm L (Pair)

From: £1,094.65
To: £1,170.16
Inc. VAT

Product Code: PCW21-3-PCW28-3

Product Images



Product Options

Product Code / Internal channel width / Overall length (cm)

PCW28-3 / Wide 25 / 300cm

£975.13



RampCentre Ultralight-Combi, unique lightweight channel ramps that are both folding and telescopic. Good for bridging door threshold with unequal levels each side and for bridging uPVC door thresholds. Overall length 300cm (9ft 10"), length of telescopic section 194cm (76"), length hinged section 106cm (42"), internal channel width 25cm (10"). Max. load (pair) 250kg (39st). Weight of each half 11.4kg (23lbs). Stored Dimensions L x W x D - 108 x 30.5 x 13cm (31 x 12 x 5"). Supplied as a pair.

PCW21-3 / Wide 25 / 210cm

£912.21



RampCentre Ultralight-Combi, unique lightweight channel ramps that are both folding and telescopic. Good for bridging door threshold with unequal levels each side and for bridging uPVC door thresholds. Overall length 210cm (6ft 11"), length of telescopic section 135cm (53"), length hinged section 75cm (30"), internal channel width 25cm (10"). Max. load (pair) 300kg (47st). Weight of each half 8kg (18lbs). Stored Dimensions L x W x D - 78 x 30.5 x 13cm (31 x 12 x 5"). Supplied as a pair.

Description

Ultralight-Combi™ are unique lightweight channel ramps that are both folding and telescopic.

The channel ramps can be used straight or folded over a threshold and offer the greatest flexibility for access.

Available in two sizes with an overall length of 210cm (6ft 11") and 300cm (9ft 10") with a wide channel width of 25cm (9.84").

Key benefits:

- Can be used straight or folded over a threshold depending on your requirements
- 5cm (2") Low kerbs and long bevel sides greatly increase clearance for scooters and power chairs
- A good choice for bridging a threshold with unequal levels each side
- Compact for storage and stowing in a vehicle
- Excellent solution for going up and over uPVC door thresholds
- The two halves can be used at different lengths from each other, great for use on cross-slopes
- Great for handling cross-slopes, where each half can be adjusted to any length and set at different

www.independent4life.co.uk | info@independent4life.co.uk | Tel: 0800 500 3001 | VAT No: 942447711

EORI GB942447711000

lengths from each other as required

- Lightweight
- Designed, manufactured, and stocked in the UK

Technical details:

- Both ramps have a wide internal track width of: 25cm (9.84")
- Both ramps have a kerb height of: 5cm (2")

Product Code: PCW21-3

- Max. length: 210cm (6ft 11")
- Telescopic length: 135cm (53")
- Hinged length: 75cm (30")
- Stored dimensions: 78 x 30.5 x 13cm (31 x 12 x 5")
- Capacity (Pair): 300kg (47st)
- Weight each half: 8kg (18lbs)

Product Code: PCW28-3

- Max. length: 300cm (9ft 10")
- Telescopic length: 194cm (76")
- Hinged length: 106cm (42")
- Stored dimensions: 106 x 30.5 x 13cm (31 x 12 x 5")
- Capacity (Pair): 250kg (39st)
- Weight each half: 11.4kg (23lbs)

Warranty:

- 2-year manufacturer warranty

Manufacturer product codes:

- PCW21-3, PCW28-3

Additional Information

Manufacturer	RampCentre
Ramp Width (cm / inches)	Int. Channel 25 / 9.84"
Application / Ramp Type	Channel Ramps (Pair)
Dead Weight (kg / lbs)	5.0 to 9.99 to 11.02 / 21.83, 10 / 22.05 to 19.99 / 44.07
Ramp Material	Aluminium
Handrails	No Handrails