



Independent 4 Life

Ultralight Telescopic 2-part, Standard 19cm Channel Ramps, Min. 75 to Max. 202cm Overall L - Pair

From:	£454.80
To:	£586.80
Inc. VAT	

Product Code: PT12-2-PT20-2

Product Images



Product Options

Product Code / Internal channel width / Min. to Max. Length (cm)



PT12-2 / Standard 19 / Min. 75 to Max. 120cm

£379.00

RampCentre Ultralight-Telescopic 2-part channel ramps that can be used when partially extended making their use flexible. The two halves can be used at different lengths from each other, great for use on cross-slopes. Internal channel width 19cm (7.5") with a minimum telescopic length of 75cm (2ft 5") to a maximum of 120cm (3ft 11"). Capacity (Pair) 400kg (63st), ramp weight each half: 3.6kg (8lbs).



PT20-2 / Standard 19 / Min. 117 to Max. 202cm L

£489.00

RampCentre Ultralight-Telescopic 2-part channel ramps extend up to 2m and can be used when partially extended making their use flexible. The channels can be used at different lengths from each other, great for use on cross-slopes and accessing 4x4's. Adjustable lengths between 117cm (3ft 10") to a maximum of 202cm (6ft 8") with a channel width of 19cm (7.5"). Capacity (Pair) 300kg (47st), ramp weight each half: 5.8kg (13lbs).

Description

Ultralight-Telescopic 2-part channel ramps extend up to 2m and can be used when partially extended making their use flexible and adaptable for different applications.

The two halves can be used at different lengths from each other, great for use on cross-slopes.

Available in two sizes with an overall length of 120cm (3ft 11") and 202cm (6ft 8") with a channel width of 19cm (7.48").

Key benefits:

- Extremely compact storage
- Ideal for vehicle access
- Versatile ramps that can be used at any length, even partly extended
- Uniquely high capacity and generous channel width
- The two halves can be used at different lengths from each other, great for use on cross-slopes
- Silent telescopic mechanism with neat safety clip to prevent opening when stored
- Designed, manufactured, and stocked in the UK

Technical details:

- All ramps have an Internal track width of: 19cm (7.48")

- All ramps have a kerb height of: 5cm (2")

Product Code: PT12-2

- Max. length: 120cm (3ft 11")
- Min. length: 75cm (2ft 5")
- Stored dimensions: 75 x 24.5 x 6cm (29 x 10 x 2")
- Capacity (Pair): 400kg (63st)
- Weight each half: 3.6kg (8lbs)

Product Code: PT20-2

- Max. length: 202cm (6ft 8")
- Min. length: 117cm (3ft 10")
- Stored dimensions: 117 x 24.5 x 6cm (46 x 10 x 2")
- Capacity (Pair): 300kg (47st)
- Weight each half: 5.8kg (13lbs)

Warranty:

- 2-year manufacturer warranty

Manufacturer product codes:

- PT12-2, PT20-2

Additional Information

Manufacturer	RampCentre
Ramp Width (cm / inches)	Int. Channel 19 / 7.48"
Application / Ramp Type	Channel Ramps (Pair)
Dead Weight (kg / lbs)	0 to 4.99 / 11.00, 5.0 to 9.99 to 11.02 / 21.83
Ramp Material	Aluminium
Handrails	No Handrails