






Independent 4 Life

# Inta Infrared Wall Mounted Tubular Tap 170mm Length (9V Mains Operated)

£324.11 Inc. VAT

Product Code: IR271CP

## Product Images



## Description

---

This Intra wall mounted tubular infrared tap delivers water without contact with the tap, with a 170mm projection length.

An ideal solution where hygiene is paramount, such as in public toilets and washrooms, where vandal resistance is required.

To avoid reflection problems keep a distance of more than 300mm between the basin and spout, this tap is not suitable for use with reflective sinks i.e. stainless steel.

### Key benefits:

- Infrared
- Vandal resistant
- Hygienic
- Water saving
- Programmable flow time
- Self adjusting sensor
- Manual temperature adjustment
- Operating pressure range of 0.5 to 8 bar
- Use with a pressure reducing valve in excess of 8 bar
- Security shut off after 90 seconds
- 9V transformer
- Self-opening after last water flow: Every 24 hours
- 6 litre per min flow regulator
- Includes an aerator that allows the water stream direction to be adjusted to prevent water splashing

### Technical details:

- Spout length (mm): 170
- Min. Inlet pressure dynamic: 0.5 bar
- Max. Inlet pressure static: 8 bar
- Max. Inlet temperature: 70°C
- Inlet connections: 10mm Spigot
- Min. Sensor range: 80mm
- Max. Sensor range: 300mm
- Security time: 90 seconds - can be reduced with a \*Remote control
- Remote control available separately if required, to adjust detection range and timed flow rate
- Power specification: 9V transformer
- Not suitable for installations, where freezing is likely

### Approvals:

- WRAS approved

### Warranty:

- 1 year manufacturer warranty

### Note:

- To limit the outlet temperature to 41°C max. use the Intamix Thermostatic Mixing Valve (Product Code 40015CP).

## Additional Information

---

|                  |  |
|------------------|--|
| Manufacturer     | Inta   |
| Application      | Basin  |
| Tap Style        | Spout, Wall Mounted Valve  |
| Mounting         | Wall   |
| Operation        | Infrared   |
| Vandal Resistant | Yes  |
| Water Pressure   | Low, Normal Mains, High Pressure Systems   |
| Approvals        | WRAS Approved  |
| Technologies     | Self Adjusting Sensor, Aerator Outlet, Water Saving, TMV a Recommended Extra, Programmable Flow Time, Mains Operated, Vandal Resistant |