

Purus SS Channel Drain 100, Tiled Floor Chess Grid, Centre Outlet, 800-2500mm Lengths




Product Code: CH1080-25CC

Product Images





Channel 100 - Length (mm) / Outlet / Grid type



Purus SS Channel 100, Tiled Floor Chess Grid, Centre Outlet - 800mm	£787.00

800mm length Purus 100 stainless steel channel drain with a chess grid for tiled floors, ideal for shower areas, changing rooms, hotels, and leisure facilities with tiled floors. For installation in timber or concrete/screed floors. Heel-safe, suitable for bare-foot areas. Centre outlet with a choice of 3x plastic wastes, horizontal and vertical outlets. Or upgrade to the Acid proof stainless steel vertical 75mm outlet.

Purus SS Channel 100, Tiled Floor Chess Grid, Centre Outlet - 1000mm

£822.00



1000mm length Purus 100 stainless steel channel drain with a chess grid for tiled floors, ideal for shower areas, changing rooms, hotels, and leisure facilities with tiled floors. For installation in timber or concrete/screed floors. Heel-safe, suitable for bare-foot areas. Centre outlet with a choice of 3x plastic wastes, horizontal and vertical outlets. Or upgrade to the Acid proof stainless steel vertical 75mm outlet.

Purus SS Channel 100, Tiled Floor Chess Grid, Centre Outlet - 1200mm

£879.00




1200mm length Purus 100 stainless steel channel drain with a chess grid for tiled floors, ideal for shower areas, changing rooms, hotels, and leisure facilities with tiled floors. For installation in timber or concrete/screed floors. Heel-safe, suitable for bare-foot areas. Centre outlet with a choice of 3x plastic wastes, horizontal and vertical outlets. Or upgrade to the Acid proof stainless steel vertical 75mm outlet.



Purus SS Channel 100, Tiled Floor Chess Grid, Centre Outlet - 1500mm

£960.00

1500mm length Purus 100 stainless steel channel drain with a chess grid for tiled floors, ideal for shower areas, changing rooms, hotels, and leisure facilities with tiled floors. For installation in timber or concrete/screed floors. Heel-safe, suitable for bare-foot areas. Centre outlet with a choice of 3x plastic wastes, horizontal and vertical outlets. Or upgrade to the Acid proof stainless steel vertical 75mm outlet.



Purus SS Channel 100, Tiled Floor Chess Grid, Centre Outlet - 2000mm

2000mm length Purus 100 stainless steel channel drain with a chess grid for tiled floors, ideal for shower areas, changing rooms, hotels, and leisure facilities with tiled floors. For installation in timber or concrete/screed floors. Heel-safe, suitable for bare-foot areas. Centre outlet with a choice of 3x plastic wastes, horizontal and vertical outlets. Or upgrade to the Acid proof stainless steel vertical 75mm outlet.

Purus SS Channel 100, Tiled Floor Chess Grid, Centre Outlet - 2500mm

£1,246.00

£1,139.00



2500mm length Purus 100 stainless steel channel drain with a chess grid for tiled floors, ideal for shower areas, changing rooms, hotels, and leisure facilities with tiled floors. For installation in timber or concrete/screed floors. Heel-safe, suitable for bare-foot areas. Centre outlet with a choice of 3x plastic wastes, horizontal and vertical outlets. Or upgrade to the Acid proof stainless steel vertical 75mm outlet.

Purus outlet



Ø50

PR640 / Low Side 50mm Outlet, 30l/min Flow Rate

Purus 100 low side outlet with 30l/min flow rate, 50mm outlet with 40mm solvent weld reducer. Includes spring loaded Nood no-odour trap. Plastic body.

PR639 / Standard 50mm Outlet, 60l/min Flow Rate

Purus 100 standard outlet with 60l/min flow rate, 50mm outlet with 40mm solvent weld reducer. Includes spring loaded Nood no-odour trap.



PR539 / Vertical 75mm Outlet, 78l/min Flow Rate

Purus 100 vertical outlet with 78l/min flow rate, 75mm outlet. Includes water trap seal. Plastic body.



PR536 / Stainless Steel Vertical 110mm

Purus 100 vertical outlet with 78l/min flow rate, 110mm outlet. Includes water trap seal. 1.4404 acid-resistant

£132.00

Description

Purus stainless steel Channel 100 drain with a Chess grid for tiled floors in shower wet areas that require longer continuous channel drains. Available in a range of lengths 800 to 2500mm, centre outlet, a choice of 3x plastic wastes with horizontal and vertical outlets. Or upgrade to the Acid-resistant stainless steel body vertical outlet. See below for more information.

Custom made lengths are available by special order, if required please contact us.

stainless steel body.

Key benefits:

• 800-2500mm lengths

- Manufactured from Premium quality 304 stainless steel
- For tiled flooring
- For installation in timber and concrete floors
- Centre waste
- Stainless steel Chess Grid
- Heel-safe ideal for bare-foot areas
- Horizontal and vertical plastic bodied wastes, with spring loaded Nood no-odour water trap
- Vertical acid-resistant stainless steel vertical waste also available
- For shower areas, changing rooms, leisure facilities, hotels
- Special order lengths, 600, 900, 1100 and 1400mm
- Bespoke custom sizes available please contact us
- Made in Sweden
- See PDF installation instructions for more information

Outlet options:

Horizontal Low - PR640:

- 30l/min flow rate
- 50mm outlet
- Includes 40mm solvent weld reducer
- Spring loaded Nood no-odour trap
- Plastic body

Horizontal Standard - PR639:

- 60l/min flow rate
- 50mm outlet
- Includes 40mm solvent weld reducer
- Water seal trap
- Plastic body

Vertical 75 - PR539:

- 78l/min flow rate
- 75mm outlet
- Water seal trap
- Plastic body

Vertical 110 - PR536:

- 78l/min flow rate
- 110mm outlet
- Water seal trap
- 1.4404 Acid-resistant stainless steel body

Warranty:

• 5 years – Must be installed in accordance with the installation instructions, and all maintenance instructions are adhered to

Product codes:

• Centre outlet: CH1080CC, CH1010CC, CH1012CC, CH1015CC, CH1020CC, CH1025CC

Manufacturer	Purus
Configuration	800mm Linear / Channel Drain, 1000mm Linear / Channel Drain, 1200mm Linear / Channel Drain, 1500mm Linear / Channel Drain, 2000mm Linear / Channel Drain, 2500mm Linear / Channel Drain
Installation	Concrete / Screed Floors, Timber Floors
Application	Screed Floors, Timber Floors
Waste Depth / Outlet Position	Centre Outlet
Flow Rate / l/min	30, 60, 78
Floor Finish	Tiled Flooring
Grate Material / Finish	Stainless Steel / Chess Grid