

AKW Braddan Level Access, Semi-recessed or Surface Mounted SHWR Tray - Choice of Size & Waste

£332.52 Inc. VAT

Product Code: BRADDAN

Product Images







Braddan installed in a screed on concrete beams or solid concrete using an AKW M11 DigiPump with a factory fitted AKW Upward discharge waste.








Braddan Cut-to-Length Kit


Cut-to-Length kit included with 1800x700mm SMC 1800 x 700 Trim-to-length Braddan trays are manufactured from SMC, supplied with a separate end cap. If the tray needs to be reduced in size to fit into an alcove the end cap then needs to be sealed to the cut end prior to the tilling flange being fitted.



Braddan Cut-to-Length Kit


1800 x 820 Trim-to-length Braddan trays are manufactured from GRP.

Supplied with trim-to-length kit comprising two lengths of aluminium extrusion. The first piece is secured to the underside of the cut end of the tray. This is then secured section is then secured over the first and sealed on top









Product Options

Tray Size (mm)	Price Inc. VAT
800×800	£345.76
820x820	£345.37
900x900	£345.37
1000x700	£332.52
1000x800	£332.52
1000x1000	£332.52
1100x800	£332.52
1200x650	£332.52
1200x700	£332.52
1200x760	£339.34
1200x820	£361.09
1200x900	£361.09
1300×700	£332.52
1300x820	£361.09
1400×900	£385.62
1420×700	£357.01
1420x820	£385.62
1500×700	£361.30
1500x820	£389.87
1600×700	£378.24
1700×700	£395.16
1800×700	£395.16
1800x820	£427.80
1800×900	£427.80

Additional Options

AKW Code / Waste option	25125 / GW19 19mm Dia. Gravity Waste	£10.47
	25126 / GW50 19mm Dia. Gravity Waste	£10.47
	25122 / PW50 Standard Pumped Waste - 15mm Outlet	£10.47
	25405 / PW50 Standard Pumped Waste - 22mm Outlet	£10.47
	07130 / Chrome Upward Discharge Waste (factory fitted)	£21.57

Description

The AKW Braddan shower tray is available in a large range of sizes and offers easy installation. The tray is 40mm thick and can be installed as a corner or alcove and is suitable for concrete, screeded and wooden floors. Create a level access, semi-recessed or a surface-mounted, low-level threshold step-in shower tray area.

The trays are unhanded with a central waste outlet with a choice of gravity and pumped wastes.

The 1800mm long trays are supplied with a 'trim to length' kit, allowing up to 300mm to be cut off. Note: trimmed trays are only suitable for alcove installations, not corners.

Create the perfect shower room with the addition of a compatible AKW shower enclosure or door set from the Larenco, Level Best, Silverdale® and Standard Screens ranges.

Key benefits:

- Suited to all floor types: Concrete, screeded and wooden floors
- Can be installed as a full level-access, semi-recessed or surface-mounted step-in shower enclosure (order shower doors or screen separately)
- The tray creates a visually defined showering area useful for those with visual impairment
- Slip resistance textured surface a safer showering experience for the user
- Excellent water drainage with a 35mm fall inside the tray
- 40mm thick multi-purpose tray
- Integral added strength for extra peace of mind
- No under tray foaming is needed for quick and easy installation
- Weight limit: 30 stone/190kg
- Non-handed shower trays for both left or right-handed installations
- Choice of gravity or pumped wastes
- Factory-fitted upward pumped waste option for unbreachable floor installations
- 1800mm trays can be cut down to 1500mm and supplied with a trim to length kit
- Three separate tiling upstands supplied. Ensures a watertight seal between tray and tiles and secure fitting of tray
- Optional pipe duct kit available to avoid the re-routing of existing pipework (order separately)
- Optional ramps: 20mm and 40mm straight/corner kits for semi-recessed and surface-mounted installations (order separately)

Waste options:

AKW: 25125 - GW19 19mm Dia. Gravity Waste

- - 19mm Water trap
- - Installation depth required below tray (mm): 93 AKW: 25126 - GW50 19mm Dia. Gravity Waste
- - 50mm Water trap
- - Installation depth required below tray (mm): 124 AKW: 25122 / 25405 - PW50 Standard Pumped Waste
- - Outlet pipe (mm): 15/22
- - Installation depth required below tray (mm): 38/44 AKW: 07130 - Chrome upward discharge (factory-fitted waste)
- - For unbreachable floor installations
- - Outlet pipe (mm): 15
- - Recommended pump AKW Digipump M11 kit without Waste (Product Code: 25471) order separately

Technical details:

- Tray height: 40mm
- Material composition:
- - GRP (Glass-reinforced plastic) all trays except:
- SMC (sheet moulded compound) 1200x700; 1200x820; 1300x700 & 1420x700mm
- Weight limit: 30 stone/190kg
- Fall to Waste: 35mm
- Suitable for Gravity and Pumped wastes
- For unbreachable floor installations, select the Upward pumped waste option
- Screen Compatibility: Larenco, Level Best, Silverdale® and Standard Screens

Optional pipe duct kits to help with installation (order separately):

- The pipe duct fits on to the tray edge to avoid the re-routing of existing pipework
- Product Code: 25038 1800mm Pipe Duct and 2 Plastic End Caps
- Product Code: 25039 1000mm Pipe Duct and 2 Plastic End Caps
- Product Code: 25049 Plastic Corner Assembly

Optional Aluminium Ramp Kits (order separately):

- The pipe duct fits on to the tray edge to avoid the re-routing of existing pipework
- Product Code: 25000 20mm Straight Ramp (length 1800mm)
- Product Code: 25002 40mm Straight Ramp (length 1800mm)
- Product Code: 25001 20mm Corner Ramp (for 900x900mm tray)
- Product Code: 25003 40mm Corner Ramp (for 900x900mm tray)
- Product Code: 25012 Made-to-Measure

Warranty:

• Lifetime Warranty (please refer to AKW's terms and conditions)

Manufacturer product codes:

- Tray only: 16522, 16470, 16472, 16000, 16528, 16071, 16196, 16360, 16006, 16012, 16045, 16520, 16013, 16050, 16022, 16058, 16063, 16495, 16531, 16442, 16028, 16039, 16065, 16099
- Tray with GW50 Gravity Waste code: 16522W, 16470W, 16472W, 16000W, 16528W, 16071W, 16196W, 16360W, 16006W, 16012W, 16045W, 16520W, 16013W, 16050W, 16022W, 16058W, 16063W, 16495W, 16531W, 16442W, 16028W, 16039W, 16065W, 16099W
- Tray with Upward Pump Waste code: 16523, 16471, 16473, 16083, 16529, 16168, 16197, 16361, 16090, www.independent4life.co.uk | info@independent4life.co.uk | Tel: 0800 500 3001 | VAT No: 942447711
 EORI GB942447711000

Additional Information

Manufacturer	AKW / Contour
Model	AKW - Braddan
Cut to Length Range (mm)	1500-1800
Tray Size (mm)	800x800, 820x820, 900x900, 1000x700, 1000x800, 1000x1000, 1100x800, 1200x650, 1200x700, 1200x760, 1200x820, 1200x900, 1300x700, 1300x820, 1400x900, 1420x700, 1420x820, 1500x700, 1500x820, 1600x700, 1700x700, 1800x700, 1800x820, 1800x900
Handing	Unhanded
Entry Configuration	Front Entry (Alcove), Corner Entry
Step-in Height (mm)	Level Access - 0, Semi-recessed - 20, Low Level Step-in - 40
Thickness of Tray (mm)	40
Waste Compatibility	Gravity Waste, Pumped Waste
Tray Edge for Floor Finish	Not Applicable
Ramp or Step Available	Ramp