




Independent 4 Life


# AKW Digipump M11 w/ Silentflow+ Waste (PGTF)

£594.05 Inc. VAT

Product Code: 25476

## Product Images





**AKW M11 DigiPump**  
Stock Code: 25470

Supply: 230V AC 50Hz 100W  
Ingress Protection: IP45  
Duty Cycle: 50% Max 30 Mins. on  
For use with electric & mixer showers.  
Pump and controller enclosed in one unit.  
Max flow rate: 11 Litres Per Minute (LPM).  
Non-handed, selectable inlet/outlet direction.  
Max Head: 1.0m (39in)  
Max Lift: 0.5m (20in)

**Contents**

1x 15mm		1x
1x 22mm		1x
1x 15mm		2x
1x 22mm		3x
3x		



## Additional Options

<b>AKW Code / Optional Flow Switch for Hot Feed</b>	25194 / Flow Sensor Kit for Dual Feed Showers	£74.51
---	---	--------

## Description

The digipump M11 electric shower kit with silentflow+ (PGTF) waste is designed to provide a quiet, reliable, and high-performance waste drainage in showering areas where gravity drainage is not achievable.

Quiet and easily serviceable this pump is designed for better removal of debris, the start up and run on settings ensures full drainage of the shower tray.

A hard-wire connection can be made to the flow sensor of ITherm electric showers and many other brands, but this also offers a wireless connection to the flow sensor within AKW SmartCare Plus Lever electric showers.

### **Key benefits:**

- For electric shower
- Extremely quiet operation
- Control box with built in test facility
- Compact making it ideal for bathrooms with limited space
- Pump head has 4 valves allowing for efficient debris removal
- Two non-return valves prevent water flowing back through the pump
- Low maintenance solution reducing inconvenience to users
- Delayed start up and run on settings
- Easy to use functionality that requires no additional effort by user
- Flow meter input automatically adjusts to variations in the water supply
- Non-handed unit - pump head can be rotated to allow flow in either direction
- A wired or wireless connections offers the installer flexibility when fitting, as this can be tailored to the space, with wireless connections eradicating the need for post-installation decorative work

### **Additional components:**

- Flow sensor kits for dual feed showers (Product Code: 25194)

### **Includes AKW 15mm Female John Guest to 22mm Male Plastic Reducer (Product Code 25195):**

- Reduces the 22mm outlet to 15mm for Digipumps

### **Includes Silentflow+ PGTF 22mm Pumped Waste for Vinyl Flooring (Product Code: 25414):**

- Pumped waste gully
- For use with AKW Tuff Form floor formers and vinyl flooring
- 22mm outlet pipe
- 48mm depth below tray
- Integrated baffles reduce the noise escaping from the chambers within the waste
- Grate opens for easy cleaning and rodding
- Grate is secured to the waste with bayonet fixings or you can screw the grate down
- Quiet performance at all flow rates
- Compatible with all AKW Pumps

### **Technical details:**

- Pump size (mm): 214 W x 311 H x 176 D
- Connectors attached width (mm): 244
- Inlet connection (mm): 15
- Outlet connection (mm): 22
- Max. outlet head 1m (39in)
- Max. inlet lift 0.5m (20in)
- Max. combined head and lift 1.5m (59in)
- Duty cycle: 30 mins max. on 50% duty (30 mins on / 30 mins off)
- On/Off, 600, 1000 (default), 2200 pulses per min
- Supply: 230V AC, 50Hz, 100W
- 24 VDC operation
- 11 litres per minute max under head/lift conditions

[www.independent4life.co.uk](http://www.independent4life.co.uk) | [info@independent4life.co.uk](mailto:info@independent4life.co.uk) | Tel: 0800 500 3001 | VAT No: 942447711

EORI GB942447711000

- 5 amp fuse
- Internal TGA fuse
- IP45 Enclosure for bathrooms
- Pump complies to BS7671

**Warranty:**

- 7 year manufacturer warranty (based upon correct installation and appropriate application)

## Additional Information

---

Manufacturer	AKW / Contour
Application	Vinyl Sheet Safety Flooring