






Independent 4 Life

Geberit AquaClean Tuma Classic WC Complete Solution, Floor-standing WC, Back-to-wall - White

£2,411.86 Inc. VAT

Product Code: 146.320.11.1

Product Images





Description

Geberit AquaClean Tuma Classic WC Complete Solution, Floor-standing WC, Back-to-wall in White. Free-standing toilet shower has a sleek design allowing for easy integration into almost any bathroom, designed to have all the basic features of a shower toilet, adjustable water spray temperature and adjustable arm position are both easily controlled by an app.

Eco-friendly, economy mode feature ensures that the toilet consumes no more than 0.5 watts causing a household to save close to 212 rolls of toilet paper per year and close to 50 pounds.

Key benefits:

- Improved personal hygiene - cleaning with water not paper
- Can be installed onto a pre-existing WC
- Rimfree ceramic pan
- App controlled
- Whirlspray technology
- Water heating by a continuous flow heater
- Geberit home app controls can deactivate the continuous flow heater
- Nozzle has pre and post rinsing with fresh water
- Oscillating spray
- Adjustable arm spray position
- Geberit home app controls for spray arm position adjustment
- Adjustable water temperature
- Geberit home app controls for water temperature adjustment
- Adjustable spray intensity
- Spray arm with nozzle can be extended
- Lid has a quick release function
- Soft opening/closing lid
- Descaling function
- Economy mode

- Compatible with Geberit Monolith
- Compatible with Geberit Home App

Technical details:

- Colour: White
- Weight Load: 150kg
- Height to the top of pan (mm): 410
- Height to top of seat (mm): 440
- Width (mm): 360
- Seat depth (mm): 523
- Overall depth (mm): 560
- Protection Degree: IPX4
- Protection Class: I
- Nominal voltage: 230 V AC
- Mains frequency: 50Hz
- Power consumption: 2000 W
- Power consumption on standby: < 0.5
- Flow pressure: 0.5 – 10 Bar
- Operating Temperature: 5 – 40°C
- Water temperature adjustment range: 34 – 40°C
- Water temperature Pre-set: 37°C
- Calculated flow rate: 0.02 l/s
- Min. flow pressure: 0.5 bar
- Spray time: 50s
- Economy mode < 0.5 W
- Spray intensity – 5 levels
- Spray arms - 5 levels
- 1 User profile
- Mains connection required
- Mains connection with flexible three-core sheathed cable, on the right side is hidden behind the WC ceramic
- Water supply connection on the left is hidden behind the WC ceramic
- Floor inlet of 60 - 280mm from wall in combination with the Geberit Monolith sanitary modules for floor-standing WC is possible
- Approved in accordance with (DIN) EN 1717 / (DIN) EN 13077

Scope of Delivery:

- Water supply connection set
- Compensation pad for WC seat
- Connection set for WC
- Sound insulation set
- Female sockets for the mains connection
- Spray shield
- 125ml of descaling agent
- Fastening materials

Manufacturer warranty:

- 2 year manufacture warranty

Please note:

- Due to the hygiene reasons this product is non-returnable

www.independent4life.co.uk | info@independent4life.co.uk | Tel: 0800 500 3001 | VAT No: 942447711

EORI GB942447711000

- Geberit will extend the warranty by one year provided that it is installed by a registered installation company and if you register the model you have purchased on their website or you send the supplied warranty card within 90 working days of the installation

Geberit Home App:

The Geberit Home App allows you to control and adjust the Geberit AquaClean shower toilets, the app can be used to register your model for a 1 year warranty extension.

- Adjusts device settings
- Users can call up user manuals digitally
- Access service and contact information
- Access care and maintenance information
- Conveniently order consumables
- Perform maintenance using step by step instructions using the app
- Firmware can be updated using the app

DOWNLOAD NOW



Apple App Store



Google Play Store

Additional Information

Manufacturer	Geberit
Brand / Model	Geberit / AquaClean Tuma Classic
Can Be Combined With	Pre-wall Mounting Frames, Geberit Monolith Front of Wall Cisterns
Colour	White
Style / Type	Back-to-wall Shower Toilet
Max. Load (kg / St)	150 / 23.5
Technical Info.	Power Supply: 230 V / 50-60hz, Water Temp Factory Settings - 37°C
Installed WC Pan Height (mm)	440
Warranty	2 Year Standard
Flush Operation	Mobile App Control
Seat Length (mm)	523
Seat Width (mm)	360
Technologies	Mains Operated, Rear Washing, 5 Levels - Water Pressure, Mobile App, Programmable User Profile x 1, Quick-release Lid, Soft Closing , Soft Opening, Adjustable Shower Spray Temp, 5 Spray Intensity Settings, 5 Spray Arm Positions, Spray Arm Extendable, Oscillating Spray, Nozzle Auto Cleaning, WhirlSpray , Rimfree WC Ceramic Pan, Economy Mode, Descaling Function