

£402.53 Inc. VAT

Inta Acura Exposed Thermostatic Sequential Control Shower Valve (Bottom Outlet)

Product Code: 90030CP

Product Images



Description

The Inta Acura exposed sequential shower control has been developed by adopting the principles of inclusive design.

As a result, the Acura delivers a shower which is suitable for any user, regardless of their sight or dexterity.

Giving you the best of both worlds, the Acura offers the ultimate balance between performance and design.

Key benefits:

- Sequential control shower valve for combined control of temperature and flow
- The shower valve has a bottom outlet ½" male shower connector, suitable for use with a flexible hose and riser rail kit
- Single piece thermal cartridge technology
- Fail safe on hot and cold supplies
- Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems
- Includes integral non return valves in the cold and hot inlet tail pieces to prevent cross contamination of the water supplies
- Chrome finish

Safety features:

• Anti-scald - thermostatic cartridge doesn't allow the water to get hot enough to scald

Approvals:

- TMV3 scheme approved
- WRAS approved

Technical details:

- Max inlet pressure (static): 10 bar
- Min inlet pressure (dynamic): 0.2 bar
- Max inlet temperature: 85°C
- Inlet connections: 15mm compression elbows
- Outlet connections: G ½" BSP
- Min temperature differential to achieve failsafe: 10°C
- Thermostatic cartridge: B091169

Warranty:

• 5 year manufacturer warranty

Please note:

- Additional check valves may be necessary in certain circumstances to comply with the Water Regulations
- With flexible hose kits, where the handset is capable of falling within 25mm of the top of the shower tray, additional backflow prevention devices may be required

Manufacturer	Inta
Shower Tupo	Direct Fed (Mixer)
Shower Type	Direct Fed (Mixer)
Shower Features	Thermostatic Mixers
Fixings	Exposed
171165	Exposed
Control	Manual Lever
Water Pressure	Low, Normal Mains, High Pressure Systems
Technologies	Thermostatic Control, Anti-Scald, Fail Safe on Hot & Cold Supplies, Temperature Control Lever, Exposed Bottom Entry
Approvals	WRAS Approved, TMV3 (Healthcare Sector)

Additional Information