

Inta Contemporary Sequential Tap

£200.63 Inc. VAT

Product Code: LO985CP

Product Images



Description

This single lever sequential spray mixer tap will provide a spray of water, giving cold to hot with 180 degrees of movement of the lever handle via a ceramic disc cartridge.

A flow regulating device incorporated within the outlet nozzle provides a maximum flow of 3.6 l/m at a pressure of 0.5 bar. For pressures under 0.5 bar the limiter insert may need to be removed to effect a suitable spray pattern. (See installation instructions for more information).

The extended lever allows the user to operate the tap with their elbow preventing contamination.

Key benefits:

- 170mm Extended lever is ideal for applications where hygiene is important
- Smooth sequential lever operated control
- Extended lever for users with limited dexterity or to avoid contact with hands
- The smooth operation of the reinforced cartridge ensures strength and durability
- Reinforced cartridge for heavy duty use

Technical details:

- Hot and cold water indicators located on head of tap
- Min operating pressure (with outlet flow limiter): 0.5 bar
- Min operating pressure (without outlet flow limiter): 0.1 bar
- Max operating pressure: 5 bar
- Flow rate (with outlet flow limiter, pressure above 0.5 bar): 3.6 l/m
- Flow rate (with outlet flow limiter removed pressure at 0.1 bar): 2.0 l/m
- Max basin thickness: 45mm
- Connections: 10mm Ø chromed copper tails

Warranty:

• 1 year manufacturer warranty

Note:

• In order to prevent scalding, the hot watwer tap should be connected to the hot water supply via a thermostatic mixing valve (TMV)

Additional Information

Manufacturer	Inta
Application	Basin
Tap Style	Deck Mixer / Filler Tap
Mounting	Basin
Operation	Turn with Lever
Water Pressure	Low, Normal Mains
Technologies	Temperature Control Lever, TMV a Recommended Extra, Ceramic Disc