




£22.81 Inc. VAT

Product Images



Description

Innovations bonding and priming agent liquid for use in promoting adhesion and reducing porosity of a variety of surfaces.

Fully compatible with the Innovations liquid tanking membrane system and the Hydromat self adhesive membranes.

Preparation:

- Ensure surface to be treated is completely dry and free of dust

Application:

- Ensure all surfaces are dry and free from debris, including dust, oil, wax and other contaminants that may effect adhesion
- Smooth or glazed surfaces should be abraded to provide a mechanical key
- Apply using a brush or roller at the recommended strength and allow to dry before tiling
- **Concrete and porous surfaces:** Apply 1 coat diluted to 3 parts water to part bonding agent
- **Plaster:** Apply 1 coat diluted to 3 parts water to part bonding agent. Then apply 2 neat coats to plaster before applying any cementitious adhesive
- **Timber:** Apply 1 coat diluted to 1 parts water to part bonding agent

Technical details:

- Pack size: 1 Litre
- Storage: Store unopened in cool dry conditions, protect from frost
- Application temperature: Between 5°C and 30°C
- The product is water based and will dry in approx. 1 hour in good drying conditions
- Health and Safety: Contains biocide, may cause an allergic skin reaction

Note:

- Can be used where damp conditions are likely, but not in areas where rising damp is present

Additional Information

Manufacturer	Wetroom Innovations
--------------	---------------------