

# P12 Pump Kit D w/ UPSW-4-22 Trap for Shower Trays (with 1x Flow Switch)

£430.82 Inc. VAT

Product Code: 05PP01D

# **Product Images**




















## **Additional Options**

Product Code / Optional Extra Flow Switch and Covers	05PP11 / Additional Flow Switch the Hot Feed of a Mixer Shower	£22.53
	05PP16 / Control Box Cover	£14.52
	05PP17 / Flow Switch Cover x1	£9.83
	05PP17x2 / Flow Switch Cover x2	£19.66

## **Description**

The P12 shower waste water pump is designed for use when gravity drainage is unavailable.

Quiet and maintenance-free, this pump will easily cope with hair, shower gels and small obstructions that would normally cause a blockage.

This version of the P12 pump is supplied with a McAlpine UPSW-4-22 Pumped Shower Tray Waste for trays with 89.50mm diameter waste outlet and can be used with any electric or mixer shower which will require an extra Flow Switch.

#### **Key benefits:**

- Peristaltic pump design
- Near silent operation
- Safe 24v DC low energy motor, with low running costs
- Control box with built in test facility

- ABS Wall plate with guick release pump bracket, minimises installation time
- Supplied with a 2 metre length of 22mm flexible pipe for improved performance
- Wastewater is pumped through a sealed tube reducing the risk of blockages
- Self-priming up to 500mm
- Pumps up to 12 litres per minute
- Variable speed transformer for precise control
- Easily adjustable run-on timer
- Match the speed of pump to flow of water
- Maintenance free design
- Not handed for easy and quick installation
- Supplied with push fit pump housing cover
- Manufactured in the UK from parts that are 100% recyclable

#### Includes a McAlpine UPSW-4 pumped waste:

- Top access, easy to clean shower tray waste
- Suits 89.50mm diameter waste outlet in shower tray
- 30mm depth, 22m outlet
- 110mm chrome plated, brass flange and petal grid fitting

#### Shower tray compatibility:

- For use with the Contour Eagle TWO shower trays
- Also compatible with other shower trays with a 89.5mm diameter waste outlet please refer to waste dimensions above for guidance
- For optimum performance of 12 litres per minute, Contour recommend the pump is installed no higher than 350mm from the top of the waste outlet to the underside of the wall plate
- The maximum length of the flexible pipe from the waste to the pump should be no more than 2m
- Can be retrofitted and is compatible with all wastes with a 22mm outlet

#### **Shower compatibility:**

- Suitable for electric showers includes 1x Flow Switch which should be installed in the cold water supply
- Suitable for mixer showers select if an additional Flow Switch (Product Code: 05PP11) for the hot water supply
- If you are installing a AKW, Redring Selectronic Premier WP, Mira Advance ATL Flex Extra or the Triton Safeguard+. order alternative 'Link' Pump Kit D (Product Code: 05PP01D-L)
- See installation instructions in the "Installation and Help Guides tab" for more information

#### **Optional covers:**

- Control Box Cover (Product Code: 05PP16)
- 1x Flow Switch Cover (Product Code: 05PP17)
- 2x Flow Switch Cover (Product Code: 05PP17x2)

#### **Technical details:**

- Actual pump size (mm): 205 W x 270 H x 180 D
- Pump housing cover size (mm): 210 W x 330 H x 190 D
- Power Consumption 36 Watts intermittent rating
- 2.5 amp Fast blow fuse
- IP65 Enclosure for bathrooms
- Pump complies to BS7671

#### Warranty:

• 7 year manufacturer warranty (based upon correct installation and appropriate application)

# **Additional Information**

Manufacturer	AKW / Contour
Application	Shower Tray